

5000HD AIR DRILL SPECIFICATIONS

Base size	39 ft (11.9 m)	45 ft (13.7 m)	51 ft (15.6 m)	57 ft (17.4 m)
# sections	3	5	5	5

Dimensions - transport

Length	29 ft (8.8 m)	29 ft (8.8 m)	29 ft (8.8 m)	29 ft (8.8 m)
Height	17 ft 6 in (5.3 m)	13 ft 6 in (4.1 m)	17 ft 6 in (5.3 m)	16 ft 11 in (5.2 m)
Width	20 ft 6 in (6.2 m)	20 ft 6 in (6.2 m)	20 ft 6 in (6.2 m)	20 ft 6 in (6.2 m)

Spacing options

9.875 in (25 cm)

Number of shanks	48	56	62	70
Working width ft (m)	39.5 ft (12 m)	46.1 ft (14.1 m)	51 ft (15.6 m)	57.6 ft (17.6 m)

12 in (30.5 cm)

Number of shanks	40	46	52	58
Working width ft (m)	40 ft (12.2 m)	46 ft (14 m)	52 ft (15.9 m)	58 ft (17.7 m)

Tyres

Dual front castors (centre section)	11 L x 15 (D)	11 L x 15 (D)	11 L x 15 (D)	11 L x 15 (D)
Rear (centre section)	11 L x 15 (D)	11 L x 15 (D)	11 L x 15 (D)	11 L x 15 (D)
Dual front castors (wing section)	9.5 L x 15 (D)	9.5 L x 15 (D)	9.5 L x 15 (D)	9.5 L x 15 (D)

Depth control Flexible frame with single-point depth setting

Press wheels options

Rubber	3 in x 22 in (7.6 cm x 55.9 cm)	Steel	3.5 in x 22 in (8.9 cm x 55.9 cm)
	4 in x 22 in (10.2 cm x 55.9 cm)		4.5 in x 22 in (11.4 cm x 55.9 cm)
	5.5 in x 22 in (14 cm x 55.9 cm)		

5500 AIR DRILL SPECIFICATIONS

Base size	60 ft (18.3 m)	70 ft (21.3 m)	80 ft (24.4 m)
------------------	----------------	----------------	----------------

Spacing options

10 in (25.4 cm)

Number of shanks	72	84	NA
Working width ft (m)	60 ft (18.3 m)	70 ft (21.3 m)	NA

12 in (30.5 cm)

Number of shanks	60	70	80
Working width ft (m)	60 ft (18.3 m)	70 ft (21.3 m)	80 ft (24.4 m)

Frame widths

Main frame	10 ft (3.1 m)	10 ft (3.1 m)	10 ft (3.1 m)
Inner wing	15 ft (4.6 m)	15 ft (4.6 m)	15 ft (4.6 m)
Outer wing	10 ft (3.1 m)	15 ft (4.6 m)	20 ft (6.1 m)
Transport width	17 ft 8 in (5.4 m)	17 ft 8 in (5.4 m)	17 ft 8 in (5.4 m)
Transport height (max)	13 ft 6 in (4.1 m)	13 ft 6 in (4.1 m)	13 ft 6 in (4.1 m)

Tyres

Centre frame castors	12.5 L x 15 (D)	12.5 L x 15 (D)	12.5 L x 15 (D)
Inner wing castors	12.5 L x 15 (D)	12.5 L x 15 (D)	12.5 L x 15 (D)
Outer wing castors	12.5 L x 15 (D)	12.5 L x 15 (D)	12.5 L x 15 (D)
Rear transport wheel*	12.5 L x 15 (D)	12.5 L x 15 (D)	12.5 L x 15 (D)

*A single tyre is used unless machine is configured with 6.5 in (16.5 cm) pneumatic, then those wheels are used for transport.

Press wheels options

Rubber	3 in x 22 in (7.6 cm x 55.9 cm)	Steel	3.5 in x 22 in (8.9 cm x 55.9 cm)
	4 in x 22 in (10.2 cm x 55.9 cm)		4.5 in x 22 in (11.4 cm x 55.9 cm)
	5.5 in x 22 in (14 cm x 55.9 cm)	Pneumatic	6.5 in (16.5 cm)

Depth control Each wing follows ground independently with flexibility front to rear with single point depth setting

Packing pressure adjustment Adjustable packing pressure