

PD 5700 Precision hoe drill specifications

Model Width	50 ft (15.2 m)	60 ft (18.3 m)	70 ft (21.3 m)
-------------	----------------	----------------	----------------

Base Size			
No. of Frame Sections	3	5	5
No. of Ranks	3	3	3

Working Widths			
10 in (25.4 cm) Spacing	50 ft (15.2 m)	60 ft (18.3 m)	70 ft (21.3 m)
12 in (30.5 cm) Spacing	50 ft (15.2 m)	60 ft (18.3 m)	70 ft (21.3 m)

Number of Openers			
10 in (25.4 cm) Spacing	60	72	84
12 in (30.5 cm) Spacing	50	60	70

Frame Widths			
Main Frame	10 ft (3.05 m)	10 ft (3.05 m)	10 ft (3.05 m)
Inner Wing	N/A	15 ft (4.57 m)	15 ft (4.57 m)
Outer Wing	20 ft (6.10 m)	10 ft (3.05 m)	15 ft (4.57 m)
Transport Width	18 ft 4 in (5.60 m)	18 ft 4 in (5.60 m)	18 ft 4 in (5.60 m)
Transport Height (Max)	16 ft 6 in (5.03 m)	16 ft 6 in (5.0 m)	16 ft 6 in (5.03 m)

Tyres			
Main Frame Castors	12.5 L x 15 FI (Dual)	12.5 L x 15 FI (Dual)	12.5 L x 15 FI (Dual)
Inner Wing Castors	N/A	12.5 L x 15 FI (Dual)	12.5 L x 15 FI (Dual)
Outer Wing Castors	12.5 L x 15 FI (Dual)	12.5 L x 15 FI (Dual)	12.5 L x 15 FI (Dual)
Rear Transport Wheels	12.5 L x 15 FI (Single)	12.5 L x 15 FI (Single)	12.5 L x 15 FI (Single)

General Specifications (All Sizes)	
Packing	Individual On Row
Packing Wheels	Packing Wheels Smooth Profile 4.8 x 8
Opener (cm)	Double-shoot – Side Band (1 7/8 in (4.8 cm) Lateral and 7/8 in (2.3 cm) Vertical separation)
Air Kits	Single or Double-shoot
Row Unit/Tyre Breakout	Fully adjustable 275 - 550 lb (125 - 250 kg)
Rank to Rank Spacing in (cm)	42.9 in (109 cm)
Frame/Ground Clearance in (cm)	30 in (76.2 cm)
Hydraulic System	High quality cylinders performing both depth and wing lift functions
Depth Control	Individual depth control
Safety Chain	Standard
Transport Locks	Standard
Rear Tow Hitch	Optional auxiliary hitch